

HG floor tile treating matrix

Treatment	Porous tiles	Non-porous tiles	(High) gloss tiles
Removal of cement residue	P11 P12	P11 P12	P11
Application of basic protection (impregnation)/ reducing porosity	P13	-	-
Protection of surface against dirt and wear	P14	P14	-
Invisible protection against dirt and staining	P15	P15	-
Regular cleaning	P17	P16 P17	P18
Intensive cleaning, remove protective layer, pre-treatment protective layer	P20	P19 P20	P19 P20
Removal of oil and grease stains	P21 P42	P21	P21



Tile cement grout and mortar remover



Remove

P12

Effective against stubborn residues

Strengthens the grout

1000 ml e

Transport and store the bottle upright.

- Medical personnel can request the data sheet via +31 36 54 94 777 • The consumer's information sheet can be obtained via www.HG.eu

contains a.o.:	
non-ionic surfactants	< 5%
perfumes	

DANGER H314- Causes severe skin burns and eye damage. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P280-** Wear protective gloves and eye protection. **P301+P330+P331- IF SWALLOWED:** rinse mouth. Do NOT induce vomiting. **P303+P361+P353- IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water [or shower]. **P305+P351+P338- IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501-** Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains: hydrogen chloride, EINECS: 231-595-7



Made in The Netherlands by HG International b.v.,
P.J. Oudweg 41, 1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

UFI: C4K8-VGWM-F00F-5VNC

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd, Weston Business Centre,
Parsonage Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744



0517101210006 2601

Products and tips? See:

HG.EU

Consumer Services?

Call: +44 (0)1279 598360

8 711577 002121 >

HG tile cement grout and mortar remover (product 12)

- strengthens the grouting

HG tile cement grout and mortar remover removes stubborn cement and mortar residues from all types of porous and non-porous tiles, flagstones and non-calciferous natural stone types such as Norwegian slate, granite and quartzite.

Directions:

1. Dissolve half a litre in 5 litres of water. For more intensive cement or mortar residues, a stronger solution can be made up to 1 litre of this product to 4 litres of water.
2. First wet the surface with clean water and then apply the solution using a floor cloth or mop.
3. Then scrub the surface well with a scrubbing brush or stiff broom. Leave to penetrate for a few minutes and then scrub again.
4. Then remove the solution from the surface with a mop, regularly rinsing the mop and wringing it out in water.
5. After that, thoroughly mop the floor again 2 or 3 times with clean water. Repeat the treatment if necessary.

Coverage: ± 20-40 m².

Attention:

Do not use on calciferous stone types. You should always start by testing the stone for sensitivity to acid by treating a small area with this product (calciferous natural stone will be damaged/ marked by this product). To prevent possible oxidation of any stainless steel parts, e.g. in the kitchen or toilet, cover these parts with masking tape before use. Ventilate the area during and after use and wipe the stainless steel thoroughly with soapy water after use of this product. Certain ceramic tiles may be slightly discoloured by this product. You should therefore first test the product in an inconspicuous place to see if discolouring occurs. Do not mix with products based on active chlorine. Using this product may make the colour of the grouting slightly lighter.