

HG artificial floor treating matrix

Treatment	Artificial flooring
Protection against wear	P77
Masking wear	P77
Regular cleaning and nourishing	P78
Intensive cleaning, remove protective layer, pre-treatment protective layer	P79

0515002210006 2601

Products and tips? See:

HG.EU
Consumer Services?
Call: +44 (0)1279 598360



floors

Vinyl cleaner

extra strong



Clean

P79

Removes stubborn dirt and grease

Powerful and safe for floors

1000 ml e

Attention: Transport and store the bottle upright. Keep in a frost-free area.

Medical personnel can request the data sheet via +31 36 54 94 777
The consumer's information sheet can be obtained via www.HG.eu

DANGER H314- Causes severe skin burns and eye damage. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P280-** Wear protective gloves and eye protection. **P301+P330+P331-** IF SWALLOWED: rinse mouth. Do NOT induce vomiting. **P303+P361+P353-** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501-** Dispose of contents and container to a hazardous or special waste collection point. Contains: sodium hydroxide CAS: 1310-73-2, Isotridecanol, ethoxylated CAS: 69011-36-5, disodium metasilicate CAS: 10213-79-3, <5% anionic surfactants, non-ionic surfactants, phosphates.



Made in The Netherlands by HG International b.v.
P.J. Oudweg 41, 1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

UFI: K5ED-1E54-K000-XPJQ

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage
Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744

relief

HG vinyl cleaner extra strong (product 79)

- removes stubborn dirt and grease

HG vinyl cleaner extra strong has been specially developed for effective removal of stubborn dirt and grease from vinyl and all types of artificial flooring such as linoleum, marmoleum, PVC and resin floors. It is also suitable for the removal of polish and other protective films, such as *HG vinyl protector (product 77)*.

Directions:

Dissolve 1 litre in half a bucket (5L) of lukewarm water and apply with a floor cloth or mop. Leave to work for approximately 10 minutes. If necessary scrub the surface well with a scrubbing brush or stiff broom. Then remove the solution from the surface with a floor cloth or mop, regularly rinsing and wringing it out in water. (A water extractor can be used if required.) After that, thoroughly mop the floor again 1 or 2 times with clean water. Repeat the treatment if necessary.

Coverage:

± 25-50 m² per diluted litre.

Attention:

When cleaning a click system floor, do not make it too wet. If you clean too wet, the seams may swell up.