

HG natural stone floor treating matrix

Granite and other acid-resistant calciferous
stone types

Marble, bluestone and other non acidic-
resistant natural stone types

Treatment

Removal of cement residue	P31	P11
Protection/impregnation against dirt and staining	P32	P32
Protection/impregnation against dirt and staining, specially for bathrooms	P35	P35
Surface protection against wear and damage to top layer	P33 P34 P44	P33 P34 P44
Invisible protection against dirt and staining	P15	P15
Regular cleaning	P37 P38	P37 P38
Intensive cleaning, remove protective layer, pre-treatment protective layer	P20 P40	P20 P40
Repair of scratches/damage to top layer of calciferous natural stone types	-	-
Removal of oil and grease stains	P21 P42	P21
Removal of coloured stains	P41	P41
Enhancement of colour indoors	P48	P48

HG®

floors

Natural stone impregnating protector



Protect

P32

Prevents penetration of moisture, dirt and grease
Also suitable for granite and marble composite

1000 ml e

Attention: Transport and store the bottle upright.
Keep in a frost-free area.

Medical personnel can request the data sheet via
+31 36 54 94 777
The consumer's information sheet can be obtained
via www.HG.eu

contains a.o.:


preservation agents: Benzisothiazolinone,
Methylisothiazolinone

EUH208- Contains Methylisothiazolinone. May
produce an allergic reaction. **P101-** If medical
advice is needed, have product container or
label at hand. **P102-** Keep out of reach of
children.

Made in The Netherlands by
HG International b.v., P.J. Oudweg 41,
1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage
Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744



0550601210006 2602

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360

HG natural stone impregnating protector (product 32)

- also for granite and marble composite
- protects against dirt and grease stains

HG natural stone impregnating protector is a special basic treatment for marble and other types of natural stone such as travertine, bluestone, hard stone etc. but is also extremely suitable for concrete tiles with pieces of natural stone incorporated, such as granite and marble composite. This unique product is absorbed deep into the pores of the stone, making it less absorbent. This prevents penetration of dirt and (grease) stains, without affecting the original character of the natural stone or sealing the floor off from moisture from below, ensuring the floor can continue to "breathe". This product does not contain silicon; it is quick drying and can be used indoors and outdoors.

Directions:

1. The surface must be completely clean and free of grease and dust. For treatments that may be required: see the HG natural stone floor treating matrix on the side of this bottle.
2. The glue/cement and grouting of new floors must be completely hardened and dry. The drying time is usually 4-6 weeks.
3. Existing floors must be completely dry after cleaning, which will take at least 3 days. Highly porous tiles, such as sandstone, will need even more time to completely get rid of the water. For this type of natural stone we recommend at least 1 week. However, if the underfloor heating is switched on, a drying time of 24 hours will be sufficient. The underfloor heating must however be switched off for at least 12 hours prior to the treatment with this product.
4. The liquid should be used undiluted and preferably applied evenly in one direction with a paint roller. On (high) gloss floors, this product must be applied and polished out using a lint-free cloth.
5. If the product has not penetrated and remains on the natural stone 10 minutes after its application, this will need to be removed immediately with a clean, lint-free cloth.
6. A second treatment is recommended for very porous tiles. This second layer can be applied about 1 hour after the first treatment.
7. The floor can be walked on about 3 hours after the last treatment, and is completely protected 12 hours after the final treatment.

Coverage: Highly porous natural stone: $\pm 10\text{-}20\text{ m}^2$ per litre. Slightly porous and high gloss natural stone: $\pm 20\text{-}50\text{ m}^2$ per litre.

Maintenance: See the HG natural stone floor treating matrix on the side of this bottle.

Tip: If a floor treated with this product is not also treated with a specific top layer protector, we recommend repeating treatment with this product every 1 to 2 years in walkways and intensively used areas. Protection of the top layer by this product will gradually be reduced as a result of general wear.

Attention: For existing floors that have previously been impregnated, it is advisable to first carry out a test patch in an inconspicuous area. This will make it possible to establish how much product needs to be applied in order to avoid applying too much and having to remove the surplus material afterwards.

