



floors

Tile stain remover

Powerful against grease and oil stains

For tiles, paving stone, natural stone,
concrete and cement

P21



500 ml

HG tile stain remover (product 21)

- for grease and oil stains
- for porous flagstone, natural stone and concrete

For the removal of grease and oil stains from tiles, paving stones, natural stone, concrete and cement. **HG tile stain remover** is also suitable for removing epoxy grouting residues.

Directions for use:

To remove spots: Shake **HG tile stain remover** well and pour it over the areas to be treated. In case of severe staining this product can be used undiluted. For less severe staining **HG tile stain remover** can be diluted to a maximum of 1:5 with (preferably) warm water. Scrub with a stiff broom or a brush. Leave to penetrate for 5 to 10 minutes and then rinse with plenty of water. For very absorbent surfaces the treatment may need to be repeated once or twice.

To remove epoxy grouting residues: Shake **HG tile stain remover** well before using and apply undiluted. Scrub briefly and then leave to penetrate for about 20 minutes and scrub again. Rinse with plenty of water.

Attention: Transport and store the bottle upright. If the floors have a protective coating, that coating may also be removed by **HG tile stain remover**. Apply (to the affected areas) a new protective coating after the treatment with **HG tile stain remover**. Avoid spattering onto painted or varnished surfaces. Remove spilled liquid immediately with plenty of water. Ventilate well when using this product.

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu



8 711577 002114 >

0516600105006
2602

Products and tips? See:
HG.EU
Consumer Services?
Call: +44 (0)1279 598360



DANGER H318- Causes serious eye damage.

H304- May be fatal if swallowed and enters airways.

H335- May cause respiratory irritation. **H336-** May cause drowsiness or dizziness. **H411-** Toxic to aquatic life with long lasting effects.

P101- If medical advice is needed, have product container or label at hand.

P102- Keep out of reach of children.

P261- Avoid breathing vapours.

P271- Use only outdoors or in a well-ventilated area.

P280- Wear protective gloves and eye protection.

P301+P310- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P331- Do NOT induce vomiting.

P501- Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Solvent naphtha (petroleum), light aromatic,

EINECS: 265-199-0, Alkyl monoethanolamide ethoxylate

EINECS: 607-851-2. > 30% aromatic hydrocarbons; 5-15%

non-ionic surfactants; < 5% anionic surfactants, phosphates;

preservation agents: 2-bromo-2-nitropropane-1,3-diol;

Made in The Netherlands by HG International b.v.,

P.J. Oudweg 41, 1314 CJ Almere, The Netherlands,

Tel.: +31 36 54 94 700

UFI: U39U-XFHH-K00H-PM4R

HG Does what it promises.

UK importer: HG UKI Ltd, Weston Business Centre,
Parsonage Road, Takeley, Essex, CM22 6PU.

Tel.: +44 (0) 1206 822 744

