


HG parquet floor treating matrix

Treatment	Parquet (varnished)
Protection of the varnish against wear	P51
Regular cleaning	P53 P54
Intensive cleaning, remove protective layer, pre-treatment protective layer	P55



Parquet and wood cleaner

extra strong



0521001210006 2602

Products and tips? See:

HG.EU
Consumer Services?
Call: +44 (0)1279 598360

Attention: Transport and store the bottle upright.
Medical personnel can request the data sheet via
+31 36 54 94 777
The consumer's information sheet can be obtained
via www.HG.eu

DANGER H314- Causes severe skin burns and eye damage.



P101- If medical advice is needed, have product container or label at hand.

P102- Keep out of reach of children.

P280- Wear protective gloves and eye protection.

P301+P330+P331- IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501- Dispose of contents and container to a hazardous or special waste collection point.

Contains: sodium hydroxide CAS: 1310-73-2, Isotridecanol, ethoxylated CAS: 69011-36-5, disodium metasilicate CAS: 10213-79-3, <5% anionic surfactants, non-ionic surfactants, phosphates.

Made in The Netherlands by HG International b.v.
P.J. Oudweg 41, 1314 CJ Almere,
The Netherlands, Tel.: +31 36 54 94 700

UFI: DFKR-6KNR-S000-7D4P

50% RECYCLED PLASTIC BOTTLE
relief

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley,
Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744

HG parquet and wood cleaner extra strong (product 55)

- removes stubborn dirt and grease

HG parquet and wood cleaner extra strong has been specially developed for the fast, easy and safe removal of stubborn dirt and grease from all types of parquet and wooden flooring. It is also suitable for removal of polish and other protective films.

Directions for use:

For normal powerful cleaning:

Dissolve 1 litre in half a bucket (5 l) of lukewarm water and apply with a floor cloth or mop. Leave to work for approximately 5 minutes. Then scrub the surface carefully with a soft scrubbing brush, if necessary. Then remove the solution from the surface with a floor cloth or mop, regularly rinsing it in water and wringing it out. (A water extractor can be used if required.) After that, thoroughly mop the floor again with clean water.

To remove stubborn dirt or old polish or other protective films: Use this product undiluted. Follow the steps described above.

Use: ± 10-15 m² per litre undiluted, ± 25-50 m² per litre diluted.

Caution: If you clean too wet, the seams may swell up.