

# HG<sup>®</sup>

## garden

# teak and other hardwood restorer

restores the natural colour, quick and easy to use.

keeps hardwood (such as teak) in top condition.

contains protection against UV and water penetration.



wooden planter



wooden garden gate



wooden decking

## HG teak and other hardwood restorer

Hardwood contains mineral elements which colour (become grey) when exposed to the elements. HG "teak and other hardwood restorer" has been specially developed for restoring the natural colour and appearance of your hardwood, and lasts for at least a full season outdoors. Additionally, this product works deeply into the pores of the wood to ensure that it enjoys years of protection against stains, UV light and drying out. HG "teak and other hardwood restorer" works quickly and is easy to apply.

### Instructions for use:

Pre-treatment of grey coloured hardwood and / or hardwood with weather stains

- 1) Treat grey coloured hardwood before hand with preferably HG "hardwood colour renovator"
- 2) Rinse off the hardwood well with clean water and allow to fully dry.

### Treating the hardwood

- 1) Cover or tape all areas which are not to be treated.
- 2) Apply HG "teak and other hardwood restorer" with a brush following the wood grain and let it soak into the hardwood.
- 3) If the hardwood is still absorbent after the HG "teak and other hardwood restorer" has been applied, then a second thin coat can be applied after 10 minutes.
- 4) Remove any surplus product with a dry fluff-free cloth.
- 5) After 24 hours the hardwood is capable of taking a load: after 48 hours the HG "teak and other hardwood restorer" is completely hardened.

**Coverage:** 10 m<sup>2</sup> per litre, depending on how much the hardwood can absorb.

### Caution:

- Only apply to unstained and unvarnished hardwood.
- The stated soaking in and drying times apply at a temperature between 15-25°C and a relative air humidity of 50-80%. If these are more unfavourable then you should allow for a longer soaking in and drying time.
- Clean brushes with turpentine before the product has dried in.
- After opening, the product can be kept for up to 2 years or more, providing it is stored in sealed packing.
- We would recommend that you also treat new hardwood. As preparation, sand paper the hardwood and clean off all dust.

### Safety Measures:


**Transport and store the bottle upright. Caution – Absorbent materials, such as rags etc, that have come into contact with this product could catch fire due to overheating during drying. Spread the used materials properly and leave them to dry in the air. Alternatively you can soak the rags in water, place them in an airtight bag, and throw them away. We do not recommend the use of spongy materials, because of the possibility of catching fire due to overheating.** Avoid contact with skin and eyes. Do not expose to flame / heat. Do not eat or drink during application.

Medical personnel can request the data sheet via +31 (0)36 54 94 777

The consumer's information sheet can be obtained via [www.HG.eu](http://www.HG.eu)

QUESTIONS ABOUT  
CLEANING AND MAINTENANCE?  
[www.HG.eu](http://www.HG.eu)

0530000107506 1410



## 750 ml e

Contains a.o:	
aliphatic hydrocarbons	>30%
perfumes	



**DANGER H226-** Flammable liquid and vapour. **H304-** May be fatal if swallowed and enters airways. **EUH066-** Repeated exposure may cause skin dryness or cracking. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P233-** Keep container tightly closed. **P301+P310-** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. **P331-** Do NOT induce vomiting. Contains: Hydrocarbons, C11-C12, isoalkanes, cyclics, < 2% aromatics EINECS; 918-167-1.

Made in The Netherlands by HG International b.v., Damsuisweg 70, 1332 EJ Almere, The Netherlands, Tel.: +31 (0)36-5494700

relief