

HG natural stone floor treating matrix

HG®

floors

Attention: Transport and store the bottle upright.
Keep in a frost-free area.

Medical personnel can request the data sheet via
+31 (0)36 54 94 777

The consumer's information sheet can be obtained
via www.HG.eu

0520101210006 2604

EUH208- Contains triisobutyl phosphate, Rosin, fumarated, polymer with glycerol, ammonium salt. May produce an allergic reaction. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. Contains: <5% phosphates, non-ionic surfactants; preservation agents: Benzisothiazolinone

Made in The Netherlands by
HG International b.v.,
P.J. Oudweg 41, 1314 CJ Almere,
The Netherlands,
Tel.: +31 36 54 94 700

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd., Weston Business Centre,
Parsonage Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744

Natural stone protector



Protect

P33

Protects against stains and wear
Adds a satin shine

1000 ml e

Treatment		
Removal of cement residue	P31	P11
Protection/impregnation against dirt and staining	P32	P32
Surface protection against wear and damage to top layer	P33 P34 P44	P33 P34 P44
Invisible protection against dirt and staining	P15	P15
Regular cleaning	P37 P38	P37 P38
Intensive cleaning, remove protective layer, pre-treatment protective layer	P20 P40	P20 P40
Repair of scratches/damage to top layer of calciferous natural stone types	-	-
Removal of oil and grease stains	P21 P42	P21
Removal of coloured stains	P41	P41
Enhancement of colour indoors	P48	P48

HG natural stone protector (product 33)

- adds shine
- protects against wear and damage to the top coat

HG natural stone protector is an easily applicable liquid polymer emulsion which forms a glossy, super-thin yet extremely strong and protective film when dry. It protects the top layer of the natural stone against wear and damage by acids such as soft drinks and wine. This protector also gives an anti-slip effect.

Directions:

1. The surface must be completely clean and free of grease and dust. For the required treatments: see the HG natural stone floor treating matrix on the side of this bottle.
2. The glue/cement and grouting of new floors must be completely hardened and dry. The drying time is usually 4-6 weeks.
3. Existing floors must be well dried after cleaning. The underfloor heating must be switched off for at least 12 hours prior to the treatment with this product.
4. Preferably apply with a wax applicator for even application (See the picture on the front of this bottle). It is also possible to use a lint-free, clean tea towel wrapped around a squeegee. On coarse floors, use a paint roller (fur roller), taking care to avoid excessive foaming during application.
5. Dilute the liquid 1:1 with cold water, then pour the liquid over the floor and apply evenly in one direction without putting pressure on the wax applicator or roller.
6. Once the product has dried (after about 40 minutes), a second layer can be applied crosswise onto the first layer.
7. The floor can be walked on about 3 hours after the final treatment and has completely hardened after 3 days.

Coverage: ± 60-80 m² per litre per layer.

Attention: In new floors which have not yet been impregnated to reduce their porosity, we recommend you first treat the floor using *HG natural stone impregnating protector (product 32)*. This protective film can be simply removed using the *HG natural stone cleaner extra strong (product 40)*. See also the HG natural stone floor treating matrix on the side of this bottle. Do not apply to surfaces treated with *HG natural stone protector (product 35)*. Only for use indoors. This product is not suitable for use on wet surfaces, such as the shower area of the bathroom.



8 711577 024697 >

0520101310006 2601

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360

