

HG parquet protector gloss (product 51)

- protects against wear and scratches

HG parquet protector gloss is a unique, easily applicable liquid polymer emulsion which forms a glossy, super-thin yet extremely strong protective film when dry. This protects the varnish layer of the parquet against wear, scratching and other damage. This protector also gives an anti-slip effect.

Directions:

1. The surface, also for new flooring, must be completely clean and free of grease and dust. Remove any old wax, polish and polymer layers. For the treatments that may be required: see the HG parquet floor treating matrix on the side of this bottle.
2. Preferably apply with a wax applicator for even application (see the neck label on the front of this bottle). It is also possible to use a lint-free, clean (tea) towel wrapped around a squeegee.
3. Pour the liquid undiluted over the floor and then apply evenly in the direction of the wood grain without putting pressure on the wax applicator or squeegee.
4. Once the product has dried (after about 60 minutes), a second layer can be applied crosswise onto the first layer.
5. The floor can be walked on about 1 to 2 hours after the final treatment and has completely hardened after 3 days.

Coverage:

± 40 m² per litre per layer.

Maintenance:

To clean the floor treated with this protective film, use *HG parquet cleaner shine restorer (product 53)*, see also the HG parquet floor treating matrix on the side of this bottle.

Tip:

This product is also available in a matt version.

In walkways where the protective film is more liable to wear, a new protective film can be quickly and easily applied over the existing layer, if necessary. In such cases, first clean the floor using *HG parquet cleaner (product 54)*.

Attention:

Wait approximately 7 days before applying this product to new varnish layers. This protective film can also be used on floors not fully varnished after laying, such as laminate or veneered parquet. We do not recommend the use of this product on such floors if the top layer is made up of composite materials (such as MDF or HDF). It could then result in swelling of the composite materials in the seams. Use the HG laminate products for these floors.