

HG®

BATHROOM

MOULD PREVENTOR



99% NATURALLY SOURCED INGREDIENTS*
50% RECYCLED PLASTIC

500 ml e

HG mould preventor

- prevents mould formation
- for tile grouts and silicon joints, plasterwork, etc.

HG mould preventor effectively closes surfaces to humidity and air which prevents mould from developing. This product is suitable for smooth and mat surfaces.

Directions: If there is already mould on the surface, remove it with *HG mould spray* first.

Clean and dry the surface properly before using *HG mould preventor*. Then cover with the liquid and leave to dry for approx. 30-60 minutes. On smooth surfaces, rub within 10 minutes of applying the liquid. Repeat the treatment 1x every 2 months. One bottle of 500 ml is sufficient for 10-12 m².

Attention: Transport and store the bottle upright. Not suitable for use on wallpaper and on porous surfaces. Caution when used on floor joints: this product makes the treated surface smoother.

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu



0548600105006 2407

*Information and tips? See:

HG.EU

EUH208- Contains Benzisothiazolinone. May produce an allergic reaction. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children.

Made in The Netherlands by
HG International b.v., P.J. Oudweg 41,
1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

HG Does what it promises.

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley, Essex,
CM22 6PU. Tel.: +44 (0) 1206 822 744