

HG laminate floor treating matrix

Treatment	Laminate
Protection against wear	P70
Regular cleaning	P71 P72 P73
Intensive cleaning, remove protective layer, pre-treatment protective layer	P74

HG®

floors

Laminate, vinyl and PVC cleaner extra strong



Clean

P74

Removes stubborn dirt and grease
Powerful and safe for floors

1000 ml e

0513401210006 2601

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360



8 711577 009427 >

Attention: Transport and store the bottle upright. Keep in a frost-free area.

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu

DANGER H314- Causes severe skin burns and eye damage.

P101- If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P280-** Wear protective gloves and eye protection. **P301+P330+P331-** IF SWALLOWED: rinse mouth. Do NOT induce vomiting. **P303+P361+P353-** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501-** Dispose of contents and container to a hazardous or special waste collection point.

Contains: sodium hydroxide CAS: 1310-73-2, Isotridecanol, ethoxylated CAS: 69011-36-5, disodium metasilicate CAS: 10213-79-3, <5% anionic surfactants, non-ionic surfactants, phosphates.
Made in The Netherlands by HG International b.v.
P.J. Oudweg 41, 1314 CJ Almere,
The Netherlands, Tel.: +31 36 54 94 700

UFI: HH3Y-UCJG-Y00V-3MXF

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley,
Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744

HG laminate, vinyl and PVC cleaner extra strong (product 74)

- removes stubborn dirt and grease

HG laminate, vinyl and PVC cleaner extra strong is a powerful cleaner for safe and effective removal of stubborn dirt, grease and protective films.

Directions for use:

For normal powerful cleaning:

Dissolve 1 litre in half a bucket (5 l) of lukewarm water and apply with a well wrung-out floor cloth or mop, rinsing it regularly in the solution. Do not rinse or mop dry, simply leave the floor to dry on its own.

To remove protective coatings:

Pour the undiluted product into a bucket and then apply using a well wrung-out mop or floor cloth. The floor must not be made too wet (see Caution). Leave to penetrate for a few minutes and then scrub with a scrubbing brush or stiff broom if required. Wipe up the liquid with a clean and well wrung-out mop, regularly rinsing it in clean water. Finally, mop the floor once or twice again with a well wrung-out mop and clean water.

Use:

± 10-15 m² per litre undiluted, ± 25-50 m² per litre diluted.

Caution:

Never use too much water when cleaning the floor, as the seams may swell when wet.