

HG parquet floor treating matrix

Treatment	Parquet (varnished)
Protection of the varnish against wear	P51
Regular cleaning	P53 P54
Intensive cleaning, remove protective layer, pre-treatment protective layer	P55



0520001210006 2601

Products and tips? See:
HG.EU
Consumer Services?
Call: +44 (0)1279 598360

8 711577 006402 >



Parquet protector gloss



Protect

P51

Protects against scratching and wear

Adds a satin shine

1000 ml e

Attention: Transport and store the bottle upright.
Keep in a frost-free area.Medical personnel can request the data sheet via
+31 (0)36 54 94 777The consumer's information sheet can be obtained
via www.HG.eu

EUH208- Contains triisobutyl phosphate, Rosin, fumarated, polymer with glycerol, ammonium salt. May produce an allergic reaction. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. Contains: <5% phosphates, non-ionic surfactants; preservation agents: Benzisothiazolinone

Made in The Netherlands by
HG International b.v.,
P.J. Oudweg 41, 1314 CJ Almere,
The Netherlands,
Tel.: +31 36 54 94 700

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd., Weston Business Centre,
Parsonage Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744

HG parquet protector gloss (product 51)

• protects against wear and scratches

HG parquet protector gloss is a unique, easily applicable liquid polymer emulsion which forms a glossy, super-thin yet extremely strong protective film when dry. This protects the varnish layer of the parquet against wear, scratching and other damage. This protector also gives an anti-slip effect.

Directions:

1. The surface, also for new flooring, must be completely clean and free of grease and dust. Remove any old wax, polish and polymer layers. For the treatments that may be required: see the HG parquet floor treating matrix on the side of this bottle.
2. Preferably apply with a wax applicator for even application (see the neck label on the front of this bottle). It is also possible to use a lint-free, clean (tea) towel wrapped around a squeegee.
3. Pour the liquid undiluted over the floor and then apply evenly in the direction of the wood grain without putting pressure on the wax applicator or squeegee.
4. Once the product has dried (after about 60 minutes), a second layer can be applied crosswise onto the first layer.
5. The floor can be walked on about 1 to 2 hours after the final treatment and has completely hardened after 3 days.

Coverage:

± 40 m² per litre per layer.

Tip:

In walkways where the protective film is more liable to wear, a new protective film can be quickly and easily applied over the existing layer, if necessary.

Attention:

Wait approximately 7 days before applying this product to new varnish layers. This protective film can also be used on floors not fully varnished after laying, such as laminate or veneered parquet. We do not recommend the use of this product on such floors if the top layer is made up of composite materials (such as MDF or HDF). It could then result in swelling of the composite materials in the seams. Use the HG laminate products for these floors.

