

HG natural stone floor treating matrix

HG®

floors

Natural stone cement grout film remover



Remove

P31

Effective and safe for floors

For all natural stone, granite and marble
composite

1000 ml e

Granite and other acid-resistant calciferous
stone types

Marble, bluestone and other non acidic-
resistant natural stone types

Treatment

Removal of cement residue	P31	P11
Protection/impregnation against dirt and staining	P32	P32
Surface protection against wear and damage to top layer	P33 P34 P44	P33 P34 P44
Invisible protection against dirt and staining	P15	P15
Regular cleaning	P37 P38	P37 P38
Intensive cleaning, remove protective layer, pre-treatment protective layer	P20 P40	P20 P40
Repair of scratches/damage to top layer of calciferous natural stone types	-	-
Removal of oil and grease stains	P21 P42	P21
Removal of coloured stains	P41	P41
Enhancement of colour indoors	P48	P48

Attention: Transport and store the bottle upright.
• Medical personnel can request the data sheet via
+31 36 54 94 777 • The consumer's information sheet
can be obtained via www.HG.eu

contains a.o.:

non-ionic surfactants, phosphonates

< 5%

WARNING H319- Causes serious
eye irritation., **P101-** If medical
advice is needed, have product
container or label at hand.,
P102- Keep out of reach
of children., **P264-** Wash
hands thoroughly after
handling. , **P305+P351+P338-**
IF IN EYES: Rinse cautiously with
water for several minutes. Remove
contact lenses, if present and easy to
do. Continue rinsing.




Made in The Netherlands by
HG International b.v., P.J. Oudweg 41,
1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

UFI: 0K69-1M1K-C006-5WAK

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley,
Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744



0521601210006 2604

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360

HG natural stone cement grout film remover (product 31)

- also for granite and marble composite

HG natural stone cement grout film remover is non-acidic and therefore safely removes cement and/or limescale residues from marble and other types of natural stone such as travertine, bluestone, hard stone etc. but is also extremely suitable for concrete tiles with pieces of natural stone incorporated, such as granite and marble composite.

Directions:

Floor cleaning:

1. Remove as much loose cement and limescale as possible beforehand.
2. Dissolve half a litre in half a bucket (5L) of water. For more intensive soiling, a stronger solution can be made of 1 litre of this product to 4 litres of water.
3. First wet the surface with clean water and then apply the solution using a floor cloth or mop. Do not treat more than 10 to 15 m² at once.
4. Scrub the surface well with a scrubbing brush, or leave to penetrate for 5 minutes and then scrub well again.
5. Remove the solution from the surface with a mop, regularly rinsing the mop and wringing it out in water. A water extractor can be used if required.
6. After that, thoroughly mop the floor again 2 or 3 times with clean water. Repeat the treatment if necessary.

Wall cleaning:

As described above. Always work from top to bottom.

Coverage:

± 30-40 m² per litre.

Attention:

Only use this product for marble and other types of calciferous natural stone. Other cement removers can seriously damage the calciferous natural stone.