

HG protective coating matt finish **(HG product 34)**

HG "protective coating matt finish" is an easily applied liquid polymer emulsion which forms a matt, super-thin yet extremely strong and protective film when dry. This protects the top layer of the natural stone against wear and damage by acids such as soft drinks and wine. This protective film also has an anti-slip effect.

Directions:

- 1) The surface must be completely clean and free of grease and dust. For the required treatments: see the HG natural stone floors treating matrix on the side of this bottle.
- 2) The glue/cement and grouting of new floors must be completely hardened and dry. The drying time is usually 4-6 weeks.
- 3) Existing floors must be well dried after cleaning. Under floor heating must be switched off for at least 12 hours prior to the treatment with this product.
- 4) Do not shake before use; instead turn the bottle upside down a number of times to mix the contents well without foaming.
- 5) Preferably apply with a waxer for even application (see the neck label on the front of this bottle). It is also possible to use a lint-free, clean tea towel wrapped around a squeegee. On coarse floors, use a paint roller (fur roller), taking care to avoid excessive foaming during application.
- 6) Pour the liquid undiluted over the floor and then apply evenly in one direction without putting pressure on the waxer or squeegee.
- 7) Once the product has dried (after about 60 minutes), a second layer can be applied in the same direction onto the first layer.
- 8) The floor can be walked on about 1 to 2 hours after the final treatment and has completely hardened after 3 days.

Use: ± 40 m² per litre per layer.

Maintenance:

For regular mopping: We recommend HG "polished tile cleaner" (HG product 38). This product cleans the floor excellently, does not damage the protective film and does not build up a glossy layer. See also the HG natural stone floors treating matrix on the side of this bottle.

Tip:

This product is also available in a glossy version.

Attention:

On new floors which have not yet been impregnated to reduce their porosity, we recommend you first treat the floor using HG "impregnator" (HG product 6) or HG "impregnating protector" (HG product 32). This protective film can be simply removed using the HG "power cleaner" (stripper) (HG product 40). See also the HG natural stone floors treating matrix on the side of this bottle. This product gives glossy natural stone a matt finish. Do not apply to surfaces treated with HG "natural stone protector" (HG product 35). Only for use indoors. This product is not suitable for use on wet surfaces, such as the shower area of the bathroom.