

# HG<sup>®</sup>

BATHROOM

## mould spray

without scrubbing  
or scouring




500 ml e

### How mould spray

- without scrubbing or scouring
- for tile grout, silicone joints, plaster etc

**HG mould spray immediately destroys fungus and algae in damp places, inside and outside.** For cleaning tiled walls (also suitable for marble) and grouting in the bathroom, shower, toilet, kitchen, cellar, basement, sauna, swimming pool, garage, shed etc.. It cleans also facades, balconies, plant boxes, garden ornaments etc. but excluding wood. **HG mould spray** bleaches grey and black mould spots and green algae spots.

**Directions for use:** Remove the locking clip before use. The product has a bleaching action. If in doubt, first test on an inconspicuous area or a discreet place. Do not remove fungi and algae before using the product. Press the nozzle at the front side and turn a quarter. Spray the surface from 3 - 5 cm distance and leave it to work for 30 minutes. In case of stubborn stains, spray again and leave to work for another 30 minutes. Clean the sprayed surface with sponge and water. Elastic grouting (for instance silicone paste) must be washed off after 30 minutes and be treated again. Turn the nozzle a quarter backwards after use (blocking position). For cleaning large surfaces with green deposits, we advise *HG algae and mould remover*.



contains a.o.:

anionic surfactants, chlorine-based bleaching agents

< 5%



PCS No.: 94357  
0518600105006  
2303

Products and tips? See:

**HG.EU**  
Consumer Services?  
Call: +44 (0)1279 598360

**Dosage:** 500 ml HG mould spray is suitable for 2-3 m<sup>2</sup> of wall surfaces, 6-8 m<sup>2</sup> of tile grout.

**Attention:** We recommend you to ventilate well during use and to wear rubber/plastic gloves. Prevent splashes on clothing, paintwork, plastic shower trays and vertical blinds. Rinse with water immediately in case of contact with skin, clothing and sensitive surfaces. Avoid contact with metals such as prints on ornamental strips, aluminium and stainless steel. Do not treat coloured surfaces. We do not recommend the use of this product on ceilings. In elastic grouting (for instance silicone paste) sometimes some permanent brown discolouration may occur after use. In badly glazed tiles and old tiles with hairline cracks brown discolouration may occur. This brown colour can possibly be removed with Hypo (Sodium thiosulfate), which can be obtained from your customer service department. Do not reuse the bottle. **Transport and store cool, dark and in an upright position.**

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via [www.HG.eu](http://www.HG.eu)

**WARNING H315-** Causes skin irritation.

**H319-** Causes serious eye irritation.

**H400-** Very toxic to aquatic life.

**EUH206-** Warning! Do not use together with other products.

May release dangerous gases (chlorine). **P101-** If medical advice

is needed, have product container or label at hand. **P102-** Keep out of

reach of children. **P264-** Wash hands

thoroughly after handling. **P273-**

Avoid release to the environment.

**P305+P351+P338-** IF IN EYES:

Rinse cautiously with water for

several minutes. Remove contact

lenses, if present and easy to

do. Continue rinsing. **P337+P313-**

If eye irritation persists: Get medical

advice/attention.

Made in The Netherlands by

HG International b.v., P.J. Oudweg 41, 1314 CJ Almere,

The Netherlands, Tel.: +31 36 54 94 700

UFI: KX3M-XH98-R00Q-GJJ3

**HG Does what it promises.**

UK importer: HG UKI Ltd,

Weston Business Centre, Parsonage Road, Takeley,

Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744

