## HG stain away 3

Directions for use: Test a small inconspicuous part of the material beforehand to check that it is colour-last. Remove as much of the stain as possible beforehand, Allow the product to work in for 10-15 minutes in a small bowt containing the product to work in for 10-15 minutes in a small bowt containing the product read allow the flight of the containing the product and allow the flight to dry. Place small stains on an absorment white surface, e, a, of which issue, and day up with a colot dampened in the product. Then rinse off well with hot water. Transport and store the bottle uppiret. \*\* Medical presonnel can request the data sheet via

## be obtained via www.HG.eu Biodegradable according to regulation 648/2004/EC



0542201300506 2402 DANGER H225- Highly flammable liquid and vapour, H304- May be fatal if swallowed and enters airways. H315- Causes skin. irritation. H317- May cause an allerdic skin reaction. H319- Causes serious eve irritation, H336- May cause drowsiness or dizziness. H410- Very toxic to aquatic life with long lasting effects. P101- If medical advice is needed, have product container or label at hand. P102- Keep out of reach of children. P233- Keep container tightly closed. P280- Wear protective gloves and eye protection, P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P331- Do NOT induce vomiting. P501- Dispose of contents and container in accordance with all local, regional. national and international regulations. Contains cyclohexane CAS: 110-82-7 propan-2-ol CAS (R)-p-mentha-1,8 diene 67-63-0 5989-27-5 Hydrocarbons, 77, malka isoalkanes, cyclics Eineo CAS: 647 49-0 Made in The Netherlands by HG national b.v., P.J. Oud leg 41, 1314 CJ Almere

The Netherlands, Tel.: +31 36 54 94 700 UFI: 0470-06AP-T100-FMEK